

## **HARDWARE FEATURES**

- Stainless steel envelope
- Multi-dimensional spray coverage
- In-line strainer
- Sealed, top-loading chamber
- Customizable fixtures available
- Built-in work station
- Casters for easy installation

### **RESULTING IN...**

- + Superior support removal
- + Evenly treated parts
- + Cycle time reduction

## **SOFTWARE FEATURES**

- Patent-pending AUTOMAT3D® platform
- Proprietary *Agitation Algorithms*
- Variable temperature (130-160°F, 54-71°C)
- Intelligent cycle times
- Customizable settings
- One-touch repeatability with recipes storage
- Preventative maintenance schedules

### **RESULTING IN...**

- + Minimized part breakage
- + Minimal operator intervention
- + Preservation of fine-feature details

## **PRODUCT SPECIFICATIONS**

### **SIZE AND WEIGHT**

Envelope: 16" L x 16" W x 14.5" H  
(41 cm x 41 cm x 37 cm)

Machine Footprint  
(closed door): 67" W x 35" D x 67" H  
(170 cm x 88 cm x 170 cm)

Approx. Weight: 850 lbs. (386 kg) empty  
1060 lbs. (481 kg) full

### **CONSUMABLES**

Detergent: PLM-201/202-SPRAY

### **FACILITIES REQUIREMENTS**

- Water in
- Drain out
- Ventilation

### **ELECTRICAL**

| US:                     | EU:                     |
|-------------------------|-------------------------|
| • Voltage: 240V 3-Phase | • Voltage: 400V 3-Phase |
| • Amperage: 30A         | • Amperage: 25A         |

### **SAFETY FEATURES**

- Emergency stop
- Door locks
- Temperature limits
- Auto-interrupt



### **POSTPROCESS TECHNOLOGIES INC.**

2495 Main Street, Suite 615, Buffalo NY 14214 USA  
info@postprocess.com +1.866.430.5354

### **POSTPROCESS TECHNOLOGIES INTERNATIONAL**

49 Impasse du Hameau, 06250 Mougins, France  
+33 (0)4 22 32 68 13